

Model		JT6331A		JT6332A		JT6333A	
Input Rating	Power	1800W		2400W		3000W	
	Voltage	0~15V	0~150V	0~15V	0~150V	0~15V	0~150V
	Current	0~36A	0~360A	0~50A	0~500A	0~50A	0~500A
	Min. operating voltage	1.4V@360A		1.4V@500A		1.4V@500A	
	Full range current Min. rising time	10uS					
CC Mode	Range	0~36A	0~360A	0~50A	0~500A	0~50A	0~500A
	Resolution	0.5mA	5mA	1mA	10mA	1mA	10mA
	Accuracy	0.03%+0.05%FS					
CV Mode	Range	0~15V	0~150V	0~15V	0~150V	0~15V	0~150V
	Resolution	0.2mV	2mV	0.2mV	2mV	0.2mV	2mV
	Accuracy	0.03%+0.02%FS					
CP Mode	Range	1800W		2400W		3000W	
	Resolution	16Bits					
	Accuracy	0.1%+0.1%FS					
CR Mode	Range	0.012Ω~50KΩ		0.006Ω~25KΩ		0.047Ω~50KΩ	
	Resolution	16Bits					
	Accuracy	0.1%+0.0012R		0.1%+0.0024R		0.1%+0.0024R	
LED Mode	Bandwidth	100kHz above					
	Rd Coefficient	0.001~1					
Dynamic Operation Mode	Range	10uS~50S					
	Resolution	2uS					
	Accuracy	1uS+20PPM					
	Slew rate	7.2A/mS~36A/uS		10A/mS~50A/uS		10A/mS~50A/uS	
Voltage Meas.	Range	0~15V	0~150V	0~15V	0~150V	0~15V	0~150V
	Resolution	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV
	Accuracy	0.015%+0.03%FS					
Current Meas.	Range	0~36A	0~360A	0~50A	0~500A	0~50A	0~500A
	Resolution	0.1mA	1mA	0.1mA	1mA	0.1mA	1mA
	Accuracy	0.015%+0.05%FS					
Ripple Meas.	Range	0~15V	0~150V	0~15V	0~150V	0~50V	0~500V
	Bandwidth	15Hz~250kHz					
	Accuracy	0.03%+1mV	0.03%+10mV	0.03%+1mV	0.03%+10mV	0.03%+1mV	0.03%+10mV

Model		JT6334A		JT6335A		JT6336A	
Input Rating	Power	1800W		2400W		3000W	
	Voltage	0~50V	0~500V	0~50V	0~500V	0~50V	0~500V
	Current	0~18A	0~180A	0~24A	0~240A	0~24A	0~240A
	Min. operating voltage	2.8V@180A		2.8V@240A		2.8V@240A	
	Full range current Min. rising time	10uS					
CC Mode	Range	0~18A	0~180A	0~24A	0~240A	0~24A	0~240A
	Resolution	0.2mA	2mA	0.5mA	5mA	0.5mA	5mA
	Accuracy	0.03%+0.05%FS					
CV Mode	Range	0~50V	0~500V	0~50V	0~500V	0~50V	0~500V
	Resolution	0.5mV	5mV	0.5mV	5mV	0.5mV	5mV
	Accuracy	0.03%+0.02%FS					
CP Mode	Range	1800W		2400W		3000W	
	Resolution	16Bits					
	Accuracy	0.1%+0.1%FS					
CR Mode	Range	0.024Ω~25KΩ		0.047Ω~50KΩ		0.024Ω~25KΩ	
	Resolution	16Bits					
	Accuracy	0.1%+0.0006R		0.1%+0.0008R		0.1%+0.0008R	
LED Mode	Bandwidth	100kHz above					
	Rd Coefficient	0.001~1					
Dynamic Operation Mode	Range	10uS~50S					
	Resolution	2uS					
	Accuracy	1uS+20PPM					
	Slew rate	3.6A/mS~18A/uS		4.8A/mS~24A/uS		4.8A/mS~24A/uS	
Voltage Meas.	Range	0~50V	0~500V	0~50V	0~500V	0~50V	0~500V
	Resolution	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV
	Accuracy	0.015%+0.03%FS					
Current Meas.	Range	0~18A	0~180A	0~24A	0~240A	0~24A	0~240A
	Resolution	0.1mA	1mA	0.1mA	1mA	0.1mA	1mA
	Accuracy	0.015%+0.05%FS					
Ripple Meas.	Range	0~50V	0~500V	0~50V	0~500V	0~50V	0~500V
	Bandwidth	15Hz~250kHz					
	Accuracy	0.03%+3mV	0.03%+30mV	0.03%+3mV	0.03%+30mV	0.03%+3mV	0.03%+30mV